

Oven Family Overview

Temperature Range 9 °F above ambient to 572 °F / 5 °C above ambient to 300 °C		120 V		208 V 3 ø Y				PID Controller Functions						Features & Options							
		Chamber Volume in cu.ft.								Constant Temperature	One Ramp	Delayed Off	Delayed On	Temperature- Depent Delayed Off	Programm- able	Fan	Com Interface	4 - 20 mA	Temperature Alarm	Access Port (mm)	Window in Door
		0.7	1.9	4.1	8.5	14.3	24.7	-----stackable-----													
ED	Drying Oven with Gravity Convection	ED 23-UL	ED 53-UL	ED 115-UL	ED 240-UL	ED 400-UL	ED 720-UL			0-99 hours						RS 422		Audio	10/30/50		
	Uniformity at 150° C	2.5	3.2	2.5	2.5	3.0	2.8														
	BINDER Part # w/o RS 422	9010-0192	9010-0131	9010-0164	-	-	-														
	BINDER Part # with RS 422	9010-0193	9010-0132	9010-0165	9010-0167	9010-0168	9010-0169														
FD	Drying Oven with Forced Air	FD 23-UL	FD 53-UL	FD 115-UL	FD 240-UL					0-99 hours					adjust			Audio	10/30/50		
	Uniformity at 150° C	2.2	2.0	1.8	2.0																
	BINDER Part #	9010-0196	9010-0128	9010-0129	9010-0130																
FED	Drying Oven with Forced Air and Timer		FED 53-UL	FED 115-UL	FED 240-UL	FED 400-UL	FED 720-UL			99h : 59 min	99h : 59 min	99h : 59 min			adjust	RS 422		Audio	10/30/50		
	Uniformity at 150° C		2.0	1.8	2.0	2.5	2.0														
	BINDER Part #		9010-0211	9010-0213	9010-0215	9010-0217	9010-0219														
FP	Programmable Drying Oven with Forced Air		FP 53-UL	FP 115-UL	FP 240-UL	FP 400-UL	FP 720-UL			99h : 59 min	99h : 59 min	99h : 59 min	20 sections	program	RS 422			Audio Visible	10/30/50		
	Uniformity at 150° C		2.0	1.8	2.0	2.5	2.0														
	BINDER Part #		9010-0175	9010-0262	9010-0264	9010-0266	9010-0268														